

19" Коммуникационный шкаф DS, (В * Ш * Г) 900 * 800 * 600мм, 18 юнит.



SCHRACK-Info

TECHNICAL DATA

- The frame, the door, the side panels, the roof plate and the base plate are made of 1.0 mm sheet metal. The mounting for the optional castors is made of 2.0 mm sheet metal. All these parts are made of DC01 quality sheet steel. The vertical rails are made of galvanised sheet metal with a thickness of 2.0mm.
- Welded powder-coated sheet steel skeleton
- Height: 18U
- Width: 800mm
- Depth: 600mm
- Colour:
 - Light Grey RAL7035.
 - frame Blue RAL5005
- Maximum Load:
 - 15-22U: 300kg
 - 27-47U: 400kg
- Degree of protection: IP20
- 4 mm thick safety glass doors with handsome swing handle. Prepared for half-cylinder type locks. Halfcylinder lock (Order-number: DV900333), Depth= 40mm, Diameter= 17mm, Fixing= M5 Screw, optional available.
- Doors hinged right. Can be changed to hinging on left.
- External hinge system allows up to 180 degree door opening angle.
- Glass doors can be replaced by optional DSRT doors (full metal or perforated, full width or double-wing).

- Removeable and lockable side-panels. Key included. For better passive cooling, side-panels can be replaced by optional perforated side-panels DSRS.
- Removeable and lockable rear-panel. Key included. Rear panel can be replaced by optional DSRT doors (glass, full or perforated metal, full width or double-wing) or by perforated rear-panel DSRR.
- 19" rails (4 pcs.) galvanised, continuously depthadjustable. Numbering of Height-Units (U) by laser for easy readability.
- In 800mm wide DS enclosures, you can choose to adjust the 19" rails to a width of 21".
- In 900, 1.000 and 1.200 mm deep DS enclosures, there is an additional pair of vertical rails installed in half depth. This makes installation of high depth accessories together with standard accessories possible at the same time.
- Space between front vertical 19"-rail and door glass at max. spacing:
 - W600 – 35mm
 - W800 – 50mm
- Space between rear vertical 19"-rail and rear panel at max. spacing:
 - W600 – 35mm
 - W800 – 55mm
- Maximum distance between vertical rails (19"-rails) in free-standing cabinets:
 - W600 x D400 – 310mm
 - W600 x D600 – 510mm
 - W600 x D800 – 710mm
 - W600 x D900 – 810mm
 - W600 x D1000 – 910mm
 - W600 x D1200 – 1110mm
 - W800 x D600 – 470mm
 - W800 x D800 – 670mm
 - W800 x D900 – 770mm
 - W800 x D1000 – 870mm
 - W800 x D1200 – 1070mm
- Maximum usable depth in free-standing cabinets when installed e.g. on shelves:
 - D400 – 375mm
 - D600 – 575mm
 - D800 – 775mm
 - D900 – 875mm
 - D1000 – 975mm
 - D1200 – 1175mm
- Spacing between vertical 19"-rails: 451 mm
- Roof construction with opening, 19" punched. Flexible covered by removable plates of different heights to allow installation of fan-units and cable-entry panels. Remaining opening can be closed by use of one these plates.
 - D400 - Opening: 6U, Covering: 1 x 4U and 1 x 2U
 - D600 - Opening: 8U, Covering: 1 x 4U and 2 x 2U
 - D800 - Opening: 10U, Covering: 2 x 4U and 1 x 2U
 - D900 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1000 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
 - D1200 - Opening: 12U, Covering: 2 x 4U and 2 x 2U
- Floor construction with opening, 19" punched. Covered by removable plate in full height.
 - D400 - Opening: 6U, Covering: 1 x 6U
 - D600 - Opening: 8U, Covering: 1 x 8U
 - D800 - Opening: 10U, Covering: 1 x 10U
 - D900 - Opening: 12U, Covering: 1 x 12U

- D1000 - Opening: 12U, Covering: 1 x 12U
- D1200 - Opening: 12U, Covering: 1 x 12U
- Roof unit assemblies can also be fitted to floor section. Optional base required.
- Cable entry possible via roof, floor and rear panel. Delivered with demountable or break-out blanking plates.
- Brush strip panel for roof (DBK24800) optional.
- Air vents for passive ventilation.
- Earthing:
 - M8-Earthing point plus 19"-Earthingset in the rear of the cabinet
 - FastOn-Earthing-connections to all dismountable parts pre-installed
- Included assembly materials:
 - 16 x Cage nuts, bolts and washers M6
 - 4 x Levelling feet
- Wide range of available accessories (bases, fan-units, cable entry panels, fixed shelves, patch panels, cable management, PDUs, doors, etc.).
- Enclosure is delivered fully-assembled on a disposable pallet.

Технические данные

Ширина нетто (мм)	800,00
Высота нетто (мм)	900,00
Глубина нетто (мм)	600,00
Вес нетто (кг)	45,30
мин. температура окружающей среды (°C)	0
макс. температура окружающей среды (°C)	40
Подходит для HE	18U-900мм
Цвет	RAL 7035 / RAL 5005 (light grey / blue)

Таблица артикулов

ОПИСАНИЕ	Номер заказа
19" Коммуникационный шкаф DS, (В*Ш*Г) 900*800*600мм, 18 юнит.	DS188060-A
опциональные принадлежности	
Полуцилиндровый замок с ключом EK 333, включая 1 ключ включая 1 потайной винт M5x16 мм V2A	DV900333S
Кабельный ввод с щеткой, 2 юнита, RAL7035	DBK24800
19" Крыша с 2-я вент-рами и термостатом, 4 юнита, RAL7035. for freestanding enclosures DS/DSZ and DSS	DLT44802-A
Боковая панель цоколя, 600мм, для DS,DSZ,DSI, RAL7035.	DSOT1260
Фронт.панель цоколя,перфориров. с фильтром,шир.800мм,RAL7035 Standschrank, RAL7035	DSOF1283

Таблица артикулов

ОПИСАНИЕ	Номер заказа
опциональные принадлежности	
19" Панель с 5-я металлическими кольцами для кабеля.	DBC14805
19" Панель с 5-я кольцами для кабеля 40*83мм, RAL7035	DBK14805
19" Полка, шир. 450мм, макс.нагр. 80кг, RAL7035,перфор-ная	DFS14845-C
19" ПЦУ, 9xSchuko,профиль алюм. 1U, 3м-кабель, RAL7035	IU070114-3
19" удлинитель, 7хрозеток+ОПН, 1.25юнита, 2м кабель, RAL7035	IU070113
2m-connector cable, RAL7035	
19" PDU, 9x Schuko, switch, 1U, 2m-cable, Black, ALU ALU Profil	Q7070114-A
19" PDU, 7x Schuko, Switch, Overvoltage protection, 1U 2m-cable, Black, ALU	Q7070113-A
IT METER LINE Свич пасс., IN:CEE 16A красн, 12C13,6роз.	HSMPP312
Держ.блоков распред.пит.для шкафов DS и DSZ шир. 800мм, 1U 1 пара = 2 шт., монтируется снаружи вертикальной рейки 19", материал для сборки входит в комплектацию	DSPDU010
Монтажный комплект, М6, квадр.гайки, болты, шайбы, по 50 шт.	DSSRA050
19" монтажная пластина, 14U, листовая сталь, с перфорацией включая винты и клетевые гайки	DMP1914
Светильник LED, на магните, 230 В перем. тока, с датчиком дверного выключателя автоматически включается при открывании двери, внешний блок питания	DTLIGHT01
Выкл.24xRJ45 10/100/1000,бесшумн.,без вентил.,внутр.ист.пит. Metal-Chassis, 19"	QLGSW2457
TOOLLESS LINE 19" патч-панель пустая, 24 мод, 1 юнит, RAL7035 Light grey, patchcord lock down	HSER0240GS