

Технический паспорт изделия : HSATA080SW

SAT-антенна 80/75см, стальн., 39дБ, складной фидер, белый

RAL7035



SCHRACK-Info

- Parabolic dishes with heavy-duty structure to endure harsh weather conditions and strict installation conditions.
- Polyester powder coating for outdoor use.
- Galvanized steel dish at high resistance for long-lasting performances and effective protections against corrosion.
- Double edging of the dish for high torsional stiffness.
- Hot-galvanized steel mount with shaped molding to adhere to the reflector disc and reduce the contact pressure enhancing the mechanical stiffness.

TECHNICAL DATA

These 80 / 75 cm Offset parabolic dishes are realized by high precision forming which guarantees a constant production quality. Effective protection against corrosion offers long-lasting durability.

Material:

- Dishes made from galvanized steel sheet. Double edging of the dish for high torsional stiffness.
- Polyester powder coating for outdoor use in 2 colors: Anthracite and White
- Hot-galvanized steel sheet mounts. Shaped molding to adhere to the reflector disc and reduce the contact pressure enhancing the mechanical stiffness.
- AZ/EL mount with zenith indicator.
- Feedarm foldable, in aluminum alloy.
- LNB-holder suitable for LNB's with Ø 23 or 40 mm

Highest performance:

- High electric performances thanks to the accurate focus.
- Diameter: 80 / 75 cm
- Material: Steel
- Gain at 12 GHz: 38,8 dB
- Mount material: Hot galvanized steel
- Suitable for Mast (Ø): 30 - 60 mm
- LNB fixing (Ø): 23 / 40 mm
- Max. Elevation: 15° - 60°

Технические данные

Длина нетто (мм)	1.000,00
Ширина нетто (мм)	780,00
Высота нетто (мм)	100,00
Вес нетто (кг)	7,00
мин. температура окружающей среды (°C)	-40
макс. температура окружающей среды (°C)	60

Таблица артикулов

ОПИСАНИЕ	Номер заказа
SAT-антенна 80/75см, стальн.,39дБ, складной фидер, белый RAL7035	HSATA080SW
опциональные принадлежности	
SAT блок с низк.ур.шума,на подкл. к 1 приемнику,подача 40мм Black	HSATL1A
SAT блок с низк.ур.шума,на подкл. к 2 приемникам,подача 40мм black	HSATL2A
SAT блок с низк.ур.шума,на подкл. к 4 приемникам,подача 40мм	HSATL4A
SAT блок с низк.ур.шума,на подкл. к 8 приемникам,подача 40мм	HSATL8A
SAT INB Quattro для подключения к мультисвитчу, подача 40 мм	HSATLSA--A
SAT держ.ПУШ,алюм.,для 3 ПУШ,рег.,дляHSAT080A/085A/100A for HSATA100Ax/HSATA085Ax/HSATA080Ax	HSATZLH3A