

Datenblatt für Artikel: HSEUBH043T

Оптоволоконный универс. кабель, А/І- DQ(ZN)ВН 4x50/125µm OM3

Drum 2100m



Technische Daten

Количество волокон	4
диаметр нетто (mm)	7,90
Diameter - Central tube (mm)	4
Primary coating (µm)	250 ± 15
Вес нетто (kg)	0,07
Suitable	Universal cable
Watertightness	Yes
Rodent protection	Yes
Predicted lifetime	> 30 Years
Crush resistance (N/m)	≤ 10000
Оболочка кабеля	LS0H-3
Flame retardancy	Pass
Halogen-free	pH ≥ 3,5 - µS/cm ≤ 100
Smoke Density	Pass

Technische Daten - Fortsetzung

Euroclass acc. to EN50575	Dca
Smoke production	s2
Droplets	d1
Acidity	a1
Temperature range - Transport/storage (°C)	-30 to +70
Temperature range - Installation (°C)	-5 to +50
Temperature range - Operation (°C)	-30 to +70
Pulling tension - Long term (N)	≤ 2500
Pulling tension - Short term (N)	≤ 5000
Bending radii cable - Static (Ø)	10 x Ø
Bending radii cable - Dynamic (Ø)	15 x Ø
Bending radii for fibres and tubes (Ø)	> 25
Mode-Field / Cladding diameter (µm)	50 ± 2,5 125 ± 1
Wavelength (nm)	850 1300
Attenuation (dB/km)	2,5 / 3,0 0,5 / 1,0
Bandwidth (MHz*km)	≥ 1500 ≥ 500
Ethernet performance 1GB (m)	900 550
Ethernet performance 10GB (m)	300 300
Numerical aperture	0,20 ± 0,015
Refractive Index	1,482 1,477

Artikeltabelle

BEZEICHNUNG	BEST.NR.
Оптоволоконный универс. кабель, А/І-DQ(ZN)ВН 4х50/125µm OM3 Drum 2100m	HSEUBH043T
опциональные принадлежности	
19" соединит.бокс, 4 волокна, LC, 50/125µm OM3, расширяемый, 1 юн.	HSELS043LG
19" соединит.бокс, 4 волокна, SC, 50/125µm OM3, расширяемый, 1 юн.	HSELS043CG
19" соединит.бокс, 4 волокна, ST, 50/125µm OM3, расширяемый, 1 юн.	HSELS043TG