

Технический паспорт изделия : QLIES0610-

DIN-рейка Выключатель 4xRJ45 (PoE+) +1xRJ45/SFP+1xSFP, 126Вт

4 x 10/100/1000Мбайт/с PoE+ (802.3at) RJ45 port, 1 x Гбайт Combo (RJ45/SFP), 1 x 100/1000Base-X SFP слот, 1 x клеммная коробка, вх. напряж. 48В пост.т.-55В пост.т., без источника питания



SCHRACK-Info

QLIES0610- Industry Ethernet Switch provides 4 PoE ports 10/100/1000Base plus 2 port Gigabit SFP to enable high speed network at mission-critical environment.

With the industrial standard DIN-rain mount: this switch can be easily installed in the cabinet, plus the clearly visible status LEDs provide simple monitoring of port link activity.

Moreover, the SFP slots support pluggable modules that enabling you to choose from a variety of transceivers. This switch is Power Sourcing Equipment (PSE), and it is fully complied with IEEE 802.3at PoE standard at maximum 30W power budget per port. It helps to save infrastructure wiring costs dramatically by eliminating electric wiring and less UPS needed. Also, it is compatible with IEEE802.3af standard PD devices.

Key-Features

- 1 x 10/100/1000Base-T PoE ports
- 1 Gigabit Combo + 1 Gigabit SFP (100/1G) slot
- PoE ports can support the IEEE 802.3at standard and power up 30W
- 1000-Mbps-Full-duplex, 10/100Mbps-Full/Half-duplex
- Auto-Negotiation, Auto-MDI/MDIX
- -40°C to 75°C (-40°F to 167°F) operating temperature range

- DIN-Rail mount installation
- Metal case design and compliant with IP30 standard
- Input power 48VDC

TECHNICAL DATA

- Standards & Protocols:
 - IEEE 802.3 10-BASE-T, Ethernet
 - IEEE 802.3u 100-BASE-TX, Fast Ethernet
 - IEEE 802.3ab 1000 Base-T, Gigabit Ethernet
 - IEEE 802.3z 1000 Base-X Gigabit Ethernet
 - IEEE 802.3x Flow Control and Back Pressure
 - IEEE 802.3af Power over Ethernet (PoE)
 - IEEE 802.3at Power over Ethernet Plus (PoE+)
- Buffer memory:
 - 1024 KB
- Plug:
 - 4 x 10/100/1000 Mbps PoE RJ45 port
 - 1 x Gigabit Combo (RJ45 / SFP)
 - 1 x 100/1000 Base-X SFP Slot
 - 1 x Terminal Block
- Button:
 - DIP1 On: Port 5 supports TX Copper
 - DIP1 Off: Port 5 supports SFP (Default)
 - DIP2: Reserved
- Indicator:
 - PW1 (Power 1): Green / PW2 (Power 2): Green / ERR (Fault): Amber
 - LNK: (RJ45): Green
 - SPD: Amber (1000) / Green (100) / Off (10)
 - SFP: Green (Link / Active)
- Transmission method:
 - Store-and-Forward
- Power consumption:
 - 48-55 VDC Dual power input capable (Redundancy)
 - Protection:
 - Polarity Reversal
 - Overload Current
- Power:
 - Alarm Relay Output 1A @ 24VDC
- Energy consumption:
 - 6 watts /with no PoE PD attached)
 - 160 watts (with full PoE PD attached)

- Backplane:
 - 12 Gbps
- MAC address table:
 - 1 K
- Data rate:
 - 10/100/1000 Mbps

Features

- PoE:
 - Power Budget: Max. 126W
 - PD classification identity
 - PoE over current protection
 - PoE circuit sorting protection
 - PoE Power Output: Max. 15.4 watts (802.3af) or 36 watts (802.3at)
 - Power Pin Assignment: 1/2(+), 3/6(-)

Performance

- Forwarding rate:
 - 1000 Mbps port - 1,488,000pps
 - 100 Mbps port - 148,000pps
 - 10 Mbps port - 14,880pps
- Jumbo-Frames:
 - 10 K

Environment

- Temperature:
 - Operating: -40°C ~ 75°C
 - Storage: -40°C ~ 85°C
- Humidity (non-condensing):
 - Storage: 5% ~ 95%
 - Operating: 5% ~ 95%
- Application:
 - Desk, wall and chassis mounted

Physical Data

- Dimensions (W x D x H):
 - 40 x 105 x 38 mm
- Weight:
 - 720 g

Reliability

- MTBF:
 - 510,304 hrs

Approval and Compliance

- Certification:
 - FCC Part 15 Subpart B Class A
 - CE
 - VCCI
- Security:
 - EN60950-1
- Housing:
 - EN61000-4-2 (ESD) Level 3
 - EN61000-4-3 (RS) Level 3
 - EN61000-4-4 (EFT) Level 3
 - EN61000-4-5 (Surge) Level 3
 - EN61000-4-6 (CS) Level 3
 - EN61000-4-8 (Magnetic Field) Level 3
 - UL508 (Pending)
 - EN 50121-4 (Pending)
 - IEC 60068-2-27
 - IEC 60068-2-32
 - IEC 60068-2-6
 - UL 508

Order Information

- QLIES0610-

Package Contents

- QLIES0610-
- Quick Installation Guide

Технические данные

Ширина нетто (мм)	40,00
Высота нетто (мм)	38,00
Глубина нетто (мм)	105,00
EAN-код	4015867188507
мин. температура окружающей среды (°C)	0
макс. температура окружающей среды (°C)	70
Продукт	Свитч для Ethernet
Скорость	10/100/1000Мб/с
Порты	6
Монтаж	U-образная шина

Таблица артикулов

ОПИСАНИЕ	Номер заказа
DIN-рейка Выключатель 4xRJ45 (PoE+)+1xRJ45/SFP+1xSFP, 126Вт 4 x 10/100/1000Мбайт/с PoE+ (802.3at) RJ45 port, 1 x Гбайт Combo (RJ45/SFP), 1 x 100/1000Base-X SFP слот, 1 x клеммная коробка, вх. напряж. 48В пост.т.-55В пост.т., без источника питания	QLIES0610
опциональные принадлежности	
S4H TOOLLESS LINE адаптер для DIN-рейки, 1 модуль Lightgrey	HSERH010GS
FO-модуль SFP 1000BaseSX LC многофункц. VCSEL 850нм, 550м for devices of the QL ... Series	QLSFP3001
FO-модуль SFP 1000BaseLX LC отдельн.функция 1310нм, 10km for devices of the QL ... Series	QLSFP3211
Промышл. источник питания, 48В пост.т., 120Вт, DIN-рейка PoE гот.	QLPOW4840
Промышл. источник питания, 48В пост.т., 480Вт, DIN-рейка PoE гот.	QLPOW4860
Ист.пит., 110В-240В пер.т.50/60Гц ; 48В пост.т./1.35А,64,8Вт	QLPOW4801
Оптическая соединительная коробка для DIN-рейки, 4 волокна, RAL7035, с кабельными выводами, муфтами	HSELS043LR
Оптическая соединительная коробка для DIN-рейки, 4 волокна, RAL7035, с кабельными выводами, муфтами	HSELS049LR
Оптическая соединительная коробка для DIN-рейки, 4 волокна, RAL7035, с кабельными выводами, муфтами	HSELS044LR