

Технический паспорт изделия : SR3PDIEM07

PDU Essential Metered; 24xC13; 6xSchuko; 400V; 16A

Measurement per phase, incl. mounting bracket with screws



SCHRACK-Info

- PDU ESSENTIAL Metered
- Metering per Phase
- Input: 16A/400V | 11 kW
- Output: 24xC13 0° IEC Socket 6xCEE7/3 35° Socket
- split into three phases
- Supply cable: 3.0m | 2,5mm²
- with CEE 16A plug, red
- Integrated function for measuring current, voltage, reactive, apparent and active power, active energy, frequency and power factor
- Hot-swappable controller
- Integrated web server with web interface
- 2x 1Gbit/s Ethernet connection
- 1x USB-A port
- 2x Interface for sensors
- 2.0" TFT color display
- incl. mounting brackets

Технические данные

Длина нетто (мм)	1.468,50
Ширина нетто (мм)	45,00
Высота нетто (мм)	60,00
Вес нетто (кг)	1,90
EAN-код	4057298233081
необязующая рекомендация цены	1.195,00
мин. температура окружающей среды (°C)	-5
макс. температура окружающей среды (°C)	45
Номинальное напряжение	400V
Степень защиты	IP20
Product typ	Metered Essential
Number of sockets	30
Outlet type	24 x IEC320 C13 und 6 x CEE7/3
Номинальный ток (A)	16
Phases per feed	3
Вид подключения	CEE 16 A red
Protocol	CLI IPv6 IPv4 DNS SMTPS SSH HTTP NTP DHCP SMTP HTTPS SNMP Trap Syslog SNMPv2/v3 Telnet
Монтаж	Bracket (L-shape)

ОПИСАНИЕ	Номер заказа
PDU Essential Metered; 24xC13; 6xSchuko; 400V; 16A Measurement per phase, incl. mounting bracket with screws	SR3PDIEM07