

Технический паспорт изделия : SR3PDIPM10

PDU PRO Metered, 30xC13, 6xC19, 400V, 32A

Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!



SCHRACK-Info

- PDU PRO Metered
- Metering per phase
- Input: 32 A / 400 V | 22 kW
- Zuleitung: 3,0 m | 4 mm²
- with CEE plug 32 A red
- Output: 30x C13 IEC Socket + 6 x C19 IEC Socket
- 6x hydraulic-magnetic circuit breakers 16 A
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped)

- Packed in cardboard box
- Length 1913 mm

Технические данные

Длина нетто (мм)	1.925,90
Ширина нетто (мм)	56,00
Высота нетто (мм)	65,00
EAN-код	4057298207945
необязующая рекомендация цены	2.484,00
мин. температура окружающей среды (°C)	0
макс. температура окружающей среды (°C)	50
Номинальное напряжение	400V
Степень защиты	IP20
Product typ	Metered
Number of sockets	36
Outlet type	30 x IEC320 C13 und 6 x IEC320 C19
Номинальный ток (A)	32
Phases per feed	3
Вид подключения	CEE 32 A red
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Монтаж	Bracket (L-shape)

ОПИСАНИЕ

Номер заказа

PDU PRO Metered, 30xC13, 6xC19, 400V, 32A

SR3PDIPM10

Measurement per phase, incl. mounting bracket with screws, not suitable for 42U enclosures or smaller!