

Технический паспорт изделия : SR3PDIPP02

PDU PRO Metered+, 36xCombo Outlets (C13, C15, C19, C21), 400V, 16A

Metering per outlet, incl. mounting bracket with screws



SCHRACK-Info

- PDU PRO Metered+
- Metering per socket
- Input: 16 A / 400 V | 11 kW
- Supply cable: 3,0 m | 2,5 mm²
- with CEE plug 16 A red
- Output: 36x Combo C13/C15/C19/C21
- Integrated function for measuring current, voltage, reactive, apparent and active power, Reactive, apparent and active energy, frequency and power factor
- Hot-swappable controller and power supply unit
- Integrated web server with web interface 1x Gbit/s (PoE) and 1x 10/100Mbit/s Ethernet connection
- Interface for PDU network (up to 20 PDUs)
- 1x RJ45 interface for up to ten external sensors
- 1x USB-C port (USB 2.0)
- 2.4" TFT color display
- Incl. frames for color coding (blue, red)
- Incl. mounting brackets (L-shaped) </I

Технические данные

Длина нетто (мм)	1.568,70
Ширина нетто (мм)	56,00
Высота нетто (мм)	71,00
EAN-код	4057298230318
необязующая рекомендация цены	3.615,00
мин. температура окружающей среды (°C)	0
макс. температура окружающей среды (°C)	50
Номинальное напряжение	400V
Степень защиты	IP20
Product typ	Metered+
Number of sockets	36
Outlet type	36 x Combo Socket (C13/C15/C19/C21)
Номинальный ток (A)	16
Phases per feed	3
Вид подключения	CEE 16 A red
Protocol	LDAP IPv6 IPv4 DNS SNMPv1 SSH HTTP SNMPv3 SNMPv2 NTP SSH2 DHCP ModBus /TCP SMTP HTTPS SNMP Trap Syslog
Монтаж	Bracket (L-shape)

ОПИСАНИЕ	Номер заказа
PDU PRO Metered+, 36xCombo Outlets (C13,C15,C19,C21), 400V, 16A Metering per outlet, incl. mounting bracket with screws	SR3PDIPP02