

Технический паспорт изделия : WSA6080302

Настенный двухдверный шкаф, IP54, В=600 Ш=800 Г=300 мм

листовая сталь, RAL7035, с монтажной панелью, с 4 замками с двойной бородкой, с 2 вырезами под панель кабельных вводов, Ш=300, Г=190 мм, тип С



SCHRACK-Info

- **Material:** Robust, cross-shaped construction which is welded from a cold-pressed sheet steel plate regardless on the enclosure size. The enclosure consists of two parts: corpus and door
- **Sheet steel thickness corpus:**
 - Single door:
 - 1.2mm: WSA3025150 to WSA8040300
 - 1.5mm: WSA8060210 to WSA1208300
 - Double door:
 - 1.2mm: WSA6080302
 - 1.5mm: WSA8012302 to WSA1410402
- **Gland plates:**
 - Blind gland plates made of 1.5mm powder-coated sheet steel
 - The cable entry is possible via gland plate openings in the bottom or the top because the enclosure can be rotated by 180°
 - The placement far back in the enclosure ensures an easy cable entry
 - A gasket to protect the degree of protection is included
 - Internal gland plates: WSA8012302, WSA8012402, WSA1006400, WSA1008400, WSA1010302, WSA1206400, WSA1208400, WSA1210302, WSA1212302, WSA1212402 and WSA1410402

- **Door:** Made of sheet steel and equipped with M6 threaded bolts for earthing
 - Sheet steel thickness:
 - 1.2mm: WSA3025150 to WSA6040300
 - 1.5mm: WSA6050210 to WSA8040300, except WSA6080300 + WSA6080302 (each 2mm)
 - 2mm: WSA6080300 + WSA6080302, as well as WSA8060210 to WSA1410402
 - All single door enclosures from WSA4040210 (H=400 W=400 D=210mm), as well as all double door enclosures are fitted with pre-assembled door-mounting profiles, which also serve for rail fastening
 - The door is secured with two and from a height of 1000mm with three hinges and has an opening angle of 130°
 - The door hinges are hidden and the door is attached with safety pins. The position of door hinges can be easily changed. The doors have a polyurethane foam seal to ensure the IP degree of protection
- **Lock:**
 - Single door:
 - 1 x sash lock with double-bit insert: WSA3025150 to WSA4060210
 - 2x sash locks with double-bit insert: WSA5030210 to WSA1008400
 - 1 x 3-point-lock with door lock: WSA1206300 to WSA1208400
 - Double door:
 - 4x sash locks with double-bit insert: WSA6080302 to WSA1010302
 - 1 x 3-point-lock with mini-swing handle: WSA1210302 to WSA1410402
 - Single door enclosures from a height of 500mm have two sash locks
 - Single door enclosures from a height of 1200mm are equipped with a 3-point rod lock and a door lock
 - Double door enclosures from a height of 600mm have four sash locks
 - Double door enclosures from a height of 1200mm are equipped with a 3-point rod lock and a mini-swing handle
 - The lock insert for all locking systems is a 5mm double-bit lock
 - The mini-swing handle with 5mm double-bit lock can be exchanged for a door lock or a swing handle for half-cylinder locks
- **Mounting plate:**
 - 2mm galvanised sheet steel
 - The mounting plate is folded on the sides to increase rigidity
 - The mounting plate is installed on welded M8 bolts inside the enclosure and can be removed for assembly and wiring
 - It comes with earthing points to establish a connection to the body of the enclosure
- **Mounting:**
 - The enclosure can be mounted directly to the wall with wall-mounting brackets WSAWB004, the degree of protection is maintained
 - Alternatively, the enclosure can be mounted directly on the desired mounting surface using screws (pay attention to the degree of protection!)
 - The four M8 diameter wall-mounting holes are arranged in the corners of the rear panel
 - Several enclosures can be mounted beside each other thanks to the small door opening radius
 - For the widths 300, 400, 500 and 600mm, there are corresponding pole attachments WSAPCLx00
- **Outdoor installation:**
 - Enclosures and accessories of WSA series meet the requirements of standard IEC 62208 for metal enclosures that allow outdoor installation
 - The standard IEC 62208 allows a certain degree of oxidation Ri1 according to ISO 4628-3 and in practice this degree of oxidation does not affect the functionality and mechanical solidity of the enclosure. The implementation of maintenance to avoid aesthetic deterioration and to prolong its useful life is recommended (see below)
 - Corrosion protection for the entire enclosure is recommended

- **Degree of protection:**
 - Single door IP66
 - Double door IP54
- **Impact protection:** IK10, IK08 for glazed doors
- **Finish:** Iron phosphate and electrostatic powder coating
- **Color:** RAL 7035 (Light grey)
- **Supply includes:**
 - Enclosure with two door-mounting profiles (from enclosure width 400mm and above)
 - Blind gland plate(s) with gasket(s) and screws
 - One key DIN 5mm
 - One mounting plate with mounting material
 - Earthing possibilities are given

Maintenance recommendations for sheet steel wall-mounted enclosures outdoor:

- Enclosures and accessories of WKT and WSA series meet the requirements of standard **IEC 62208** for metal enclosures that allow outdoor installation
- The standard IEC 62208 allows a certain degree of **oxidation Ri1** according to **ISO 4628-3** and in practice this degree of oxidation does not affect the functionality and mechanical solidity of the enclosure. The implementation of maintenance to avoid aesthetic deterioration and to prolong its useful life is recommended
- **Interval:** Annually
- **Visual inspection:** Detection of any harm to the surface such as scrapes or impacts that could have damaged the paint coating
- **Initial signs of rust:** Due to scrapes, impacts or any other causes
 - Remove the surface rust
 - Abrade the surface rust to get rid of it completely
- **Cleaning:** Clean the affected area with alcohol or an evaporating cleaner
- **Paint:** Paint the affected surface with a synthetic paint (RAL 7035)
 - We recommend our grey textured paint color RAL 7035, Art.-nr. IU008106




Технические данные

Ширина нетто (мм)	800,00
Высота нетто (мм)	600,00
Глубина нетто (мм)	300,00
Вес нетто (кг)	29,50
мин. температура окружающей среды (°C)	-40
макс. температура окружающей среды (°C)	100

Технические данные - Продолжение

Supply includes	Complete enclosure + mounting plate + gland plates + double bit key + accessory pack
Норма	EN 62208
Степень защиты	IP54
Класс защиты	I
Ударопрочность	IK10
Номинальное напряжение	1000V AC / 1500V DC
Цвет	RAL 7035 (светло-серый)
Ширина (мм)	800
Высота (мм)	600
Глубина (мм)	300
Толщина стенки корпуса (мм)	1,20
Монтажные панели	оцинкованная листовая сталь 2 мм
Толщина стенок монтажной пластины (мм)	2
Ширина монтажной пластины (мм)	750
Высота монтажной пластины (мм)	575
Толщина стенок двери (мм)	2
Нагрузка на одну дверь (кг)	25
Количество дверей	2
Тип	Настенный корпус из листовой стали
Общая нагрузка (кг)	175
Нагрузочная способность монтажной плиты (кг)	150
Количество сальниковых пластин	2
Укрепление двери	включено
Замок	4
Петля	4
Сальниковая пластина Тип	C
Ширина сальниковой пластины (мм)	300
Глубина сальниковой пластины (мм)	190
Монтаж на задней стенке	4
Потеря мощности (W)	-256,00

Dimension Drawing



Technical Details

Article number	Enclosure			Wall thickness		DR	Clearance depth D1	Doors		Gland plates				Rear panel	Mounting plate		
	(mm)			(mm)											(mm)		
	H	W	D	Corpus	Door	(mm)	(mm)	locks	hinges	WG (mm)	DG (mm)	Type	Pcs.	Number of fixings	HM	WM	DM
WSA6080302	600	800	300	1.2	2	2x 315	284	4	4	300	190	C	2	4	575	750	12
WSA8012302	800	1200	300	1.5	2	2x 515	284	4	4	520	100	K	2	4	775	1150	12
WSA8012402	800	1200	400	1.5	2	2x 515	383	4	4	520	200	L	2	4	775	1150	12
WSA1010302	1000	1000	300	1.5	2	2x 415	284	4	4	420	100	H	2	4	975	950	12

Таблица артикулов

ОПИСАНИЕ	Номер заказа
Настенный двухдверный шкаф, IP54, В=600 Ш=800 Г=300 мм листовая сталь, RAL7035, с монтажной панелью, с 4 замками с двойной бородкой, с 2 вырезами под панель кабельных вводов, Ш=300, Г=190 мм, тип С	WSA6080302
опциональные принадлежности	
LED lighth for EC, infra (not available in this country)	IU006519CZ
Настенные кронштейны для шкафов WSA, КП=4 шт. galvanized, PU=4 pieces	WSAWB004
Плетеный кабель заземления, длина 260 мм, неподключ.	WSTCUF260
Панель-переходник WSA для типа С с 1 вырезом под панель кабельных вводов, для WSA5040300, WSA6040300, WSA6080300, WSA6080302, WSA8040300, WSA8080300, WSA1008300 и WSA1208300	WSAVBF05
Панель кабельных вводов WSA тип С, 20 вводов кабельные вводы 9xM16, 5xM20, 4xM25, 2xM32 с заглушками, вырез под панель кабельных вводов Ш=300 Г=190 мм	WSAFA0C1
Панель кабельных вводов WSA тип С, с полиуретановым уплотнением подходит для WSA5040300, WSA6040300, WSA6080300, WSA6080302, WSA8040300, WSA8080300, WSA1008300 и WSA1208300	WSAMFR0C
Плнтус, передняя и задняя части, Ш=600, В=100 мм, листовая сталь RAL7012, КП=2 шт.	ATSOB061
Плнтус WSA, передняя и задняя части (пара), Г=300 В=100 мм листовая сталь, RAL7012	WSASOT031
Крепёж IP65, for half cylinder 40mm	IU001925
Цилиндрический замок EK 333 с 2 ключами	DV905333-A
Цилиндрический замок створки	WSSL3844-A
Дверной монтажный профиль WSA для Ш=800, до В=1000 мм КП=1 шт.	WSACP0800
Дверной выключатель WSA 6 A/230 В~, IP40 1 нормально разомкнутый (Н.Р.) и 1 нормально замкнутый контакт (Н.З.), пластиковый	WSADSW01
Фиксатор двери WSA, подходит для всех размеров	WSADSTP2
Козырек от дождя WSA Ш=800 Г=300 мм подходит для WSA6080300, WSA6080302, WSA8080300, WSA1008300 и WSA1208300	WSAD8030
Двустворч.дверь WSA из листовой стали для В=600 и Ш=800 мм подходит для WSA6080302	WSASD0608D